





	889 Female Cordsets	889 Male Cordsets	889 Patchcords	898/1485 Splitters	879 Y-Cables
Description	<ul style="list-style-type: none"> • Cable with integral female connector on one end 	<ul style="list-style-type: none"> • Cable with integral male connector on one end 	<ul style="list-style-type: none"> • Cable with integral connector on each end 	<ul style="list-style-type: none"> • Cable with single male connector attached to two female connectors 	<ul style="list-style-type: none"> • Cable with single male connector attached to two female connectors
Features	<ul style="list-style-type: none"> • Straight or right angle • Multiple standard lengths • Braided and unbraided • Standard and LED versions • Female connector provides direct interface to sensors and other field devices 	<ul style="list-style-type: none"> • Straight or right angle • Multiple standard lengths • Male connector provides interface to distribution boxes or DC micro ArmorBlock DeviceNet I/O 	<ul style="list-style-type: none"> • Straight or right angle • Multiple standard lengths • Direct connection between field devices and distribution boxes or Allen-Bradley ArmorBlock DeviceNet I/O 	<ul style="list-style-type: none"> • Straight or right angle female connectors • Multiple standard lengths • Direct connection between field devices and distribution boxes or Allen-Bradley ArmorBlock DeviceNet I/O 	<ul style="list-style-type: none"> • Straight or right angle female connectors • Multiple standard lengths • Direct connection between field devices and distribution boxes or Allen-Bradley ArmorBlock DeviceNet I/O
Available Models	<ul style="list-style-type: none"> • Mini 3-8 • Mini Illuminated . . . 3-10 • Mini Coiled 3-11 • Mini-Plus 3-24 • DC Micro 3-36 • DC Micro Illuminated 3-40 • DC Micro Coiled . . . 3-39 • AC Micro 3-67 • AC Micro Coiled . . . 3-69 • EAC Micro 3-81 • Pico 3-85 • Pico Illuminated . . . 3-84 • M23 3-105 	<ul style="list-style-type: none"> • Mini 3-12 • DC Micro 3-45 • AC Micro 3-70 	<ul style="list-style-type: none"> • Mini to Mini 3-13 • Mini-Plus 3-28 • DC Micro 3-46 • DC Micro to Pico . . . 3-49 • DC Micro to Mini . . . 3-51 • AC Micro 3-71 • Pico 3-89 • M23 3-106 	<ul style="list-style-type: none"> • DC Micro Splitter . . . 3-52 • AC Micro Splitters . . 3-74 • Pico Splitter 3-93 • DC Micro to Pico Splitter 3-94 	<ul style="list-style-type: none"> • DC Micro to DC Micro Y-Cables 3-55 • DC Micro to Conductor Y-Cables 3-55 • DC Micro to Pico Y-Cable 3-95

					
	888 Receptacles	889/1485 Bulkhead Pass-Thru	898 Distribution Boxes	871/889 Terminal Chambers	889/1485 Accessories
Description	<ul style="list-style-type: none"> • Panel mount connector with flying lead 	<ul style="list-style-type: none"> • Panel mount connector, male to female 	<ul style="list-style-type: none"> • Factory prewired distribution module connecting 4, 6, or 8 devices through a single cable. 	<ul style="list-style-type: none"> • Field installable connectors 	<ul style="list-style-type: none"> • Sealing caps, coupling adaptors, and other connection systems accessories
Features	<ul style="list-style-type: none"> • Male and female configurations • 1/2in NPT, 1/4in NPT or M14 threads • Threaded metal housing 	<ul style="list-style-type: none"> • 4- and 5-pin configurations • 1/2in NPT, 1/4in NPT or M14 threads • Threaded metal housing 	<ul style="list-style-type: none"> • 4, 6, or 8 port, parallel-wired • Cable or quick-disconnect main connection • Standard and LED versions 	<ul style="list-style-type: none"> • Screw, solder or insulation displacement connector styles • Straight or right angle • Multiple sizes for varying cable jacket diameters 	<ul style="list-style-type: none"> • Rugged durable construction • Versions to interface with male or female connectors • Multiple sizes for various connector types
Available Models	<ul style="list-style-type: none"> • Mini Receptacle . . . 3-13 • DC Micro 3-57 • AC Micro 3-75 • EAC Micro 3-83 • Pico 3-97 • M23 3-107 	<ul style="list-style-type: none"> • Mini Bulkhead Pass-thru 3-22 • DC Micro Bulkhead Pass-thru 3-65 	<ul style="list-style-type: none"> • Mini 3-17 • Mini Illuminated . . . 3-17 • DC Micro 3-59 • DC Micro Illuminated 3-59 • AC Micro 3-77 • Pico Illuminated . . . 3-99 	<ul style="list-style-type: none"> • Mini 3-19 • DC Micro 3-63 • AC Micro 3-80 • Pico 3-103 • M23 3-108 	<ul style="list-style-type: none"> • Sealing caps 3-109 • Coupling adaptors 3-110 • Mounting nuts . . . 3-110 • Sealing washers . . 3-110

Allen-Bradley PLCs