



Allen-Bradley Fiber-Optic Converter Module

(Cat. No. 1771-AF)

Documentation Update

Use this document with:

Product Data, publication 1771-2.90 - March, 1986

Important: This document supplements the data sheet listed above. Keep this update with the data sheet and make the following corrections to it.

Corrections to 1771-2.90:

The caption in figure 1 that reads: 6500 feet max. should read: 6500 feet maximum distance with continuous 100/140 um fiber-optic cable.

The specifications section should read:

Module Location

- Single slot in 1771 I/O chassis

Operating Temperature

- 0 – 60°C
- 32 – 140° F

Storage Temperature

- -40 – 85° C
- -40 – 185° F

Humidity – (Non-condensing)

- 5 – 95%

Power Supply Requirement

- +5 VDC @ 600mA from backplane

Configurations

- Point-to-point or star

Maximum Fiber Distance Between Module Pairs

- 6500 ft (2km) of continuous 100/140 um fiber-optic cable

Maximum Distance

- 43,000 ft combination of twinaxial and 100/140 um fiber-optic cable

Maximum Twinaxial Distance Between Module Pairs (Twinaxial Repeater)

- 10,000 ft of twinaxial cable per module pair (30,000 ft maximum)

Receiver Sensitivity (Optical)

- -24dBm at the end of a 1 meter 100/140 um fiber-optic cable

Optical Wavelength

- 820 nm

Fiber-optic Cable Connector Required

- SMA-905 connector

Recommended Connector Loss Guidelines

- 1dB or less per connector. This value has been included in the transmitter power (optical) specification.

Minimum Fiber-optic Cable Bandwidth Required

- 17MHz/km

Transmitter Power (Optical)

- -21.0 dBm at the end of a 1 meter 50/125 um fiber-optic cable
- -16.1 dBm at the end of a 1 meter 62.5/125 um fiber-optic cable
- -14.1 dBm at the end of a 1 meter 85/125 um fiber-optic cable
- -12.6 dBm at the end of a 1 meter 100/140 um fiber-optic cable
- -5.6 dBm at the end of a 1 meter 200/230 um fiber-optic cable

Cable Characteristics

Cable Diameter	Attenuation (dB loss/km)	Numerical Aperture (NA)	Length Guidelines (km)
50/125 um	4 dB/km	0.20 NA	0.50 km
62.5/125 um	4 dB/km	0.28 NA	1.75 km
85/125 um	4 dB/km	0.26 NA	2 km
100/140 um	5 dB/km	0.30 NA	2 km
200/230 um	6 dB/km	0.37 NA	2 km



As a subsidiary of Rockwell International, one of the world's largest technology companies — Allen-Bradley meets today's challenges of industrial automation with over 85 years of practical plant-floor experience. More than 11,000 employees throughout the world design, manufacture and apply a wide range of control and automation products and supporting services to help our customers continuously improve quality, productivity and time to market. These products and services not only control individual machines but integrate the manufacturing process, while providing access to vital plant floor data that can be used to support decision-making throughout the enterprise.

With offices in major cities worldwide

WORLD HEADQUARTERS
 Allen-Bradley
 1201 South Second Street
 Milwaukee, WI 53204 USA
 Tel: (1) 414 382-2000
 Telex: 43 11 016
 FAX: (1) 414 382-4444

EUROPE/MIDDLE EAST/AFRICA HEADQUARTERS
 Allen-Bradley Europe B.V.
 Amsterdamseweg 15
 1422 AC Uithoorn
 The Netherlands
 Tel: (31) 2975/43500
 Telex: (844) 18042
 FAX: (31) 2975/60222

ASIA/PACIFIC HEADQUARTERS
 Allen-Bradley (Hong Kong) Limited
 Room 1006, Block B, Sea View Estate
 28 Watson Road
 Hong Kong
 Tel: (852) 887-4788
 Telex: (780) 64347
 FAX: (852) 510-9436

CANADA HEADQUARTERS
 Allen-Bradley Canada Limited
 135 Dundas Street
 Cambridge, Ontario N1R 5X1
 Canada
 Tel: (1) 519 623-1810
 FAX: (1) 519 623-8930

LATIN AMERICA HEADQUARTERS
 Allen-Bradley
 1201 South Second Street
 Milwaukee, WI 53204 USA
 Tel: (1) 414 382-2000
 Telex: 43 11 016
 FAX: (1) 414 382-2400