



FLEX Ex Thermocouple/RTD Input Module

3- and 4-Wire Specification The FLEX Ex thermocouple/RTD input module (Cat. No. 1797-IRT8/A, Revision C01, F/W Rev. D) signal input range is listed at 0 to 500 Ω while the product is only capable of an input range of 0 to 485 Ω .

Also, the PT200A range is -200 to 380°C instead of -200 to 400°C.
The PT200E range is -200 to 377°C instead of -200 to 400°C.

These are changes from what was previously published.

Note: 2-wire mode operates correctly at the published specifications.

The firmware in this product is not upgradeable. Please contact Rockwell Automation Technical Support at (440) 646-5800 for assistance.

Reach us now at www.rockwellautomation.com

Wherever you need us, Rockwell Automation brings together leading brands in industrial automation including Allen-Bradley controls, Reliance Electric power transmission products, Dodge mechanical power transmission components, and Rockwell Software. Rockwell Automation's unique, flexible approach to helping customers achieve a competitive advantage is supported by thousands of authorized partners, distributors and system integrators around the world.

Americas Headquarters, 1201 South Second Street, Milwaukee, WI 53204, USA, Tel: (1) 414 382-2000, Fax: (1) 414 382-4444
European Headquarters SA/NV, avenue Herrmann Debroux, 46, 1160 Brussels, Belgium, Tel: (32) 2 663 06 00, Fax: (32) 2 663 06 40
Asia Pacific Headquarters, 27/F Citicorp Centre, 18 Whitfield Road, Causeway Bay, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846

Publication 1797-5.4-RN2 - May 2000



**Rockwell
Automation**

PN 957345-25

© 2000 Rockwell International Corporation. Printed in the U.S.A.