

IEC: IP66

FOR USE ON A FLAT SURFACE OF A TYPE 4 OR 13 ENCLOSURE

OPTION
EN OPTION
OPTION
OPCION
OPZIONE

	$\varnothing 40, \varnothing 60$		$\varnothing 60, \varnothing 90$																		
<table border="1"> <tr> <td>30 (13/16)</td> <td>48 (157/64)</td> <td>40/60 (137/64-23/8)</td> <td>50/60 (131/32-23/8)</td> <td>60/90 (23/8-335/64)</td> </tr> </table>	30 (13/16)	48 (157/64)	40/60 (137/64-23/8)	50/60 (131/32-23/8)	60/90 (23/8-335/64)																
30 (13/16)	48 (157/64)	40/60 (137/64-23/8)	50/60 (131/32-23/8)	60/90 (23/8-335/64)																	
<table border="1"> <tr> <td>800E-A2L</td> <td>800E-A4L</td> <td>40 (137/64)</td> <td>50 (131/32)</td> <td>40 (137/64)</td> <td>50 (131/32)</td> <td>40/60 (137/64-23/8)</td> <td>50/60 (131/32-23/8)</td> <td>60/90 (23/8-335/64)</td> </tr> <tr> <td>800E-A3L</td> <td></td> <td colspan="2">50 (131/32)</td> <td colspan="2"></td> <td colspan="2">50/60 (131/32-23/8)</td> <td></td> </tr> </table>	800E-A2L	800E-A4L	40 (137/64)	50 (131/32)	40 (137/64)	50 (131/32)	40/60 (137/64-23/8)	50/60 (131/32-23/8)	60/90 (23/8-335/64)	800E-A3L		50 (131/32)				50/60 (131/32-23/8)					
800E-A2L	800E-A4L	40 (137/64)	50 (131/32)	40 (137/64)	50 (131/32)	40/60 (137/64-23/8)	50/60 (131/32-23/8)	60/90 (23/8-335/64)													
800E-A3L		50 (131/32)				50/60 (131/32-23/8)															

