



THE CIRCUIT IS TYPICAL OF A SIZE 1-2 BUL 2106 FVR STARTER WITH 120 VOLT SEPARATE CONTROL

- OPTIONS:
- 1 N.O. AUXILIARY CONTACT ON THE DISCONNECT
 - 1 SURGE SUPPRESSOR ON EACH STARTER COIL

A COMPLETE AND ACCURATE REPRESENTATION OF THE CIRCUIT DEPENDS ON THE SIZE AND OPTIONS ORDERED.

NOTES

[1] REMOTE DEVICE

[2] ADDITIONAL CONTROL CIRCUIT OVERCURRENT PROTECTION MAY BE REQUIRED WHEN THE CONTROL CIRCUIT CONDUCTORS EXTEND BEYOND THE ENCLOSURE. REFER TO NATIONAL ELECTRICAL CODE.

References		BUL. 2106 SIZE 1-2	
Revision		TYPE B	
Release	Dimensions Apply Before Surface Treatment		
1 06/15/01	Dimensions in Inches Tolerances Unless Otherwise Specified		
	2 Place Decimal ± .02		
	3 Place Decimal ± .005		
	Angles ± 1		
Refer. Book		Dr.	Date
		Chkd.	Date
		Appd.	Date

Allen-Bradley
Rockwell Automation

Sheet 1 Of 1
 Dwg Size C 2106WB005