


THE CIRCUIT IS TYPICAL OF A SIZE 1-2 BUL 2123E TS2W STARTER WITH 120 VOLT SEPARATE CONTROL OPTIONS:

- 1 N.O. AUXILIARY CONTACT ON EACH STARTER
- 1 N.O. AUXILIARY CONTACT IN THE CIRCUIT BREAKER

A COMPLETE AND ACCURATE REPRESENTATION OF THE CIRCUIT DEPENDS ON THE SIZE AND OPTIONS ORDERED.

NOTES

[1] REMOTE DEVICE



| NEMA STANDARD MOTOR CONNECTIONS | | | | | | |
|---------------------------------|-------|-----|-----|------|-----|-----|
| SPEED | LINES | | | OPEN | | |
| | L1 | L2 | L3 | T11 | T12 | T13 |
| LOW | T1 | T2 | T3 | T11 | T12 | T13 |
| HIGH | T11 | T12 | T13 | T1 | T2 | T3 |

[3] ADDITIONAL CONTROL CIRCUIT OVERCURRENT PROTECTION MAY BE REQUIRED WHEN THE CONTROL CIRCUIT CONDUCTORS EXTEND BEYOND THE ENCLOSURE. REFER TO NATIONAL ELECTRICAL CODE.

INTERNAL CB DEVICES SUPPLIED WITH UNMOUNTED CONNECTION BLOCKS.

| References | | BUL. 2123E SIZE 1-2 | |
|-------------|---|---------------------|--|
| Revision | | TYPE B | |
| Release | Dimensions Apply Before Surface Treatment | | |
| 1 08/20/01 | Tolerances Unless Otherwise Specified | | |
| | 2 Place Decimal ± .02 | | |
| | 3 Place Decimal ± .005 | | |
| | Angles ± 1 | | |
| Refer. Book | Dr. | Date | |
| | Chkd. | Date | |
| | Appd. | Date | |

Sheet 1 Of 1
Dwg Size C 2123EWB005
P.C.P. AutoCAD