



NOTES

1 REMOTE DEVICE



| SPEED | LINES | | | OPEN | | |
|-----------|-------|-----|-----|------|-----|-----|
| | L1 | L2 | L3 | T11 | T12 | T13 |
| LOW FOR. | T1 | T2 | T3 | T11 | T12 | T13 |
| HIGH FOR. | T11 | T12 | T13 | T1 | T2 | T3 |
| LOW REV. | T3 | T2 | T1 | T11 | T12 | T13 |

3 ADDITIONAL CONTROL CIRCUIT OVERCURRENT PROTECTION MAY BE REQUIRED WHEN THE CONTROL CIRCUIT CONDUCTORS EXTEND BEYOND THE ENCLOSURE. REFER TO NATIONAL ELECTRICAL CODE.



| | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|--|
| X | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | TB | |
| | A | | | | | | | | | | | | | | | | | | | | | |

| |
|-----|
| T1 |
| T2 |
| T3 |
| T11 |
| T12 |
| T13 |

TB

THE CIRCUIT IS TYPICAL OF A SIZE 1-2 BUL 2126J TSR2W STARTER WITH 120 VOLT SEPARATE CONTROL OPTIONS:

- 1 'HIGH-LOW-OFF-REV' SELECTOR SWITCH
- 1 'HIGH' PILOT LIGHT (RED)
- 1 'LOW' PILOT LIGHT (RED)
- 1 'FORWARD' PILOT LIGHT (RED)
- 1 'REVERSE' PILOT LIGHT (RED)
- 1 N.O. AUXILIARY CONTACT ON EACH STARTER
- 1 N.C. AUXILIARY CONTACT ON EACH STARTER
- 1 N.O. AUXILIARY CONTACT ON THE DISCONNECT SWITCH

A COMPLETE AND ACCURATE REPRESENTATION OF THE CIRCUIT DEPENDS ON THE SIZE AND OPTIONS ORDERED.

| | | | | |
|-------------|--|---------------------|------|--------------|
| References | | BUL. 2126J SIZE 1-2 | | |
| Revision | | TYPE B | | |
| Release | Dimensions Apply Before Surface Treatment | | | |
| 1 09/05/01 | Dimensions in Inches Tolerances Unless Otherwise Specified | | | |
| | 2 Place Decimal ± .02 | Dr. | Date | Sheet 1 Of 1 |
| | 3 Place Decimal ± .005 | Chkd. | Date | Dwg Size C |
| Refer. Book | Angles ± 1 | Appd. | Date | 2126JWB004 |