



NOTES

- 1 REMOTE DEVICE
- 2 REFER TO DRIVE USER MANUAL FOR APPLICATION DATA.
- 3 CHOKE HAS 5 TURN(S) PER PHASE.

DRIVE LEGEND

- TB1 TERMINAL BLOCKS
- △ TB2 TERMINAL BLOCKS

2 BUL. 1305 ADJUSTABLE FREQUENCY AC DRIVE

THE CIRCUIT IS TYPICAL OF A 1 HORSEPOWER BUL 2162M AC DRIVE UNIT WITH BUL 1305 AC DRIVE OPTIONS:

- A 480/120V CONTROL TRANSFORMER WITH PRIMARY FUSES
- 1 'RUN' PILOT LIGHT (RED)
- 1 DeviceNET COMMUNICATION MODULE
- 1 HUMAN INTERFACE MODULE (HIM) WITH OPTIONS LISTED ABOVE

A COMPLETE AND ACCURATE REPRESENTATION OF THE CIRCUIT DEPENDS ON THE RATING AND OPTIONS ORDERED.

References		BUL. 2162M 1.0HP AC DRIVE		
Revision	Release	Dimensions Apply Before Surface Treatment	NEMA 1	
1	08/20/01	Dimensions in Inches Tolerances Unless Otherwise Specified		
		2 Place Decimal ± .02		
		3 Place Decimal ± .005		
		Angles ± 1		
Refer. Book		Dr.	Date	Sheet 1 Of 1
		Chkd.	Date	Dwg Size C
		Appd.	Date	2162MWB003