



NOTES

- [1] REMOTE DEVICE
- [2] REFER TO DRIVE USER MANUAL FOR APPLICATION DATA.
- [3] CHOKE HAS 5 TURN(S) PER PHASE.

DRIVE LEGEND

- TB1 TERMINAL BLOCKS
- △ TB2 TERMINAL BLOCKS
- TB3 TERMINAL BLOCKS

[2] BUL. 1336 PLUS II ADJUSTABLE FREQUENCY AC MOTOR DRIVE

THE CIRCUIT IS TYPICAL OF A 5 HORSEPOWER BUL 2162P AC DRIVE UNIT WITH BUL 1336 PLUS II AC DRIVE OPTIONS:

- A 480/120V CONTROL TRANSFORMER WITH PRIMARY FUSES
- 115V AC CONTROL LOGIC INTERFACE BOARD
- 1 'RUN' PILOT LIGHT (RED)
- 1 DeviceNET COMMUNICATION MODULE
- 1 HUMAN INTERFACE MODULE (HIM) WITH OPTIONS LISTED ABOVE

A COMPLETE AND ACCURATE REPRESENTATION OF THE CIRCUIT DEPENDS ON THE RATING AND OPTIONS ORDERED.

References		BUL. 2162P 5.0HP AC DRIVE		
Revision	Release	Dimensions Apply Before Surface Treatment	NEMA 1	
1	08/20/01	Dimensions in Inches Tolerances Unless Otherwise Specified	Dr.	Date
		2 Place Decimal ± .02	Chkd.	Date
		3 Place Decimal ± .005	Appd.	Date
Refer. Book		Angles ± 1		
			Sheet	1 Of 1
			Dwg Size	C
			2162PW001	