

| | |
|--|-----------|
| Quick Selection Guide | page 4–2 |
| Technical Definitions and Terminology | page 4–3 |
| Introduction | page 4–5 |
| Products | |
| 875C General Purpose Tubular | page 4–9 |
| 875CP Plastic Barrel Tubular | page 4–13 |
| 875L Limit Switch Style | page 4–19 |
| Accessories | |
| Mounting Brackets, Sight Glass Style | page 4–22 |
| Sensor Wells | page 4–23 |
| Catalog Number Index | page 9–1 |
| Comprehensive Product Index | page 10–1 |

Capacitive Proximity Sensors
Quick Selection Guide

Bulletin 875C and 875CP



| | | |
|-------------------------|--|--------------------|
| Description | Tubular Style | |
| | Plastic Face/Threaded Nickel-Plated Brass Barrel Plastic Face/Threaded Plastic Barrel Plastic Face/Smooth Plastic Barrel | |
| Diameter | 12, 18, 30, 34mm | |
| Connections | <ul style="list-style-type: none"> • Cable (PVC) • Micro Quick-Disconnect • Pico Quick-Disconnect | |
| Available Models | Type | Page Number |
| | DC 3-Wire | 4-10 |
| | DC 3-Wire Plastic Barrel | 4-13 |
| | AC 2-Wire | 4-16 |

Bulletin 875L



| | | |
|-------------------------|--|--------------------|
| Description | Limit Switch Style | |
| | Plastic Body/Multi-position Head | |
| Size | 40mm x 40mm x 120mm | |
| Connections | <ul style="list-style-type: none"> • Conduit/Terminal | |
| Available Models | Type | Page Number |
| | DC 3-Wire | 4-20 |